


PREMIUM R-134 REFRIGERANT WITH XYCLEEN™ SYSTEM CLEANER AND SYSTEM-SAFE LEAK SEALER

FOR ALL FACTORY INSTALLED AND RETROFITTED R-134A SYSTEMS
COMPATIBLE WITH ALL LUBRICANTS & RESIDUES OF R-12

- Removes and dispenses sediment in A/C system for increased cooling capacity.
- Safely seals most leaks on hoses, gaskets, and O-rings.
- Traps moisture and prevents rust
- Contains lubricant enhancing additives for smoother, quieter performance.

Contents: 11 oz. R-134a Refrigerant (1,1,1,2 Tetrafluoroethane)
2 oz. lubricant (Polyol Ester), O-ring conditioner, *Xycleen™* A/C cleaner, and
System-safe Leak Sealer



Xycleen™ removes and then prevents the redeposit of sediment in an A/C System. A cleaner system means a cooler, more efficient A/C.

INSTRUCTIONS: Shake can well. Prepare can for charging using *Interdynamics* R-134a dispensing valve and hose. Connect to low pressure port.

WARNINGS: Keep out of reach of children! • Do not run your engine in a closed garage! Do not connect to high side service port as can may burst! • Can contents under pressure. **Do not store cans inside a vehicle.** Cans will burst above 120°F. Do not puncture or incinerate. • Wear gloves and safety goggles! **FIRST AID:** If sprayed into eyes or skin, flush with plenty of warm water. Get medical attention immediately. Product can cause frostbite. • If swallowed or inhaled see a physician immediately. Do not give epinephrine if inhaled.